

RR PRIMER[®] - PU

PRODUCT

RR PRIMER[®]-PU is a monolithic adhesion promoter which ensures the cohesion of the materials intended for surface repair and cementitious sealants based on polyurethane or epoxy.

PREPARATION OF APPLICATION

The substrate concrete must be completely dry and cured, free of dust, grease, oil, and other products that possess characteristics of releasing agents.

APPLICATION

RR PRIMER[®]-PU should be applied by brush or roller in a thin layer with a pause for its drying between 10 and 15 minutes for sealant application.

PHYSICAL PROPERTIES

| | |
|-----------------|--------------------------|
| Aspect | Transparent liquid |
| Specific Weight | 0.810 kg/cm ³ |
| Drying time | 10 to 15 minutes |

CONSUMPTION

100 to 200 mL for each 50 linear meters at a depth of 10 mm, between the two internal lateral.

YIELD

Can vary depending on temperature and porosity of the concrete.

PACKAGE

3.6 liter can.

TOOL CLEANING

Clean tools with solvent-type thinner.

CLEANLINESS AND SAFETY

Users should use protective glasses and rubber gloves. Direct contact with the skin should be avoided (can cause irritation).

In case of contact with skin or eyes, wash immediately and abundantly with water, consult a doctor and inform the type of product.

Keep packages out of the reach of children, animals and sources of heat.

STORAGE

Should be stored in a dry, ventilated place and at a temperature of 77F (25C).

VALIDITY

9 months in sealed package.