

Self-Adhesive Bitumen Tape

RR FITA FLEX – MULTIUSO

PRODUCT

RR Fita Flex is a membrane of asphalt composite, self-adherent, finished with resistant aluminum and a peel-off protective film. It has easy application and excellent adhesion on most types of surfaces.

SEGMENTS OF USE

- Seals in general
- Gutters and flashings
- Air conditioning sealing and wind turbines
- Roof coverings
- Repairs of galvanized and cement roofs
- Repairs of truck trailers and containers

ADVANTAGES

- Clean, easy and practical application
- High resistance to the environment
- Great reflectivity to the sun's rays
- Great thermal and acoustic comfort
- Great adherence for glue, joints and seals
- Permanent waterproofing
- Can be used for repairs in general

APPLICATION

To obtain best results, it's recommended that the surface be free of dust, free of moisture and oils. Start the application of the tape, removing the non-stick film. It is necessary to apply the tape to make a uniform tension and constant pressing so as not leave air bubbles. For better grip in temperature below 18C it is recommended to use primer (**Baldran Flex**[®]).

Application temperature: 5C (41F) to 50C (122F).

YIELD

1.15 m/m²

CHARACTERISTICS

Main function	Glue, Seals and Joints
Chemical base	Petroleum and aluminum
Aspect	Blanket
Color	Black aluminized
Density	1.02 to 1.10 g/mL

PACKAGING

Rolls of:	Boxes with:
0.05 m x 10 m	36 rolls
0.10 m x 10 m	16 rolls
0.15 m x 10 m	12 rolls
0.20 m x 10 m	8 rolls
0.30 m x 10 m	8 rolls
0.45 m x 10 m	4 rolls
0.94 m x 10 m	unit

INDIVIDUAL PROTECTION EQUIPMENT

Glasses and PVC gloves

CLEANLINESS AND SAFETY

Keep in closed package out of the reach of children and animals and sources of heat. In case of contact with the skin or eyes, wash immediately with abundant water.

VALIDITY AND STORAGE

12 months from date of manufacture stored in a dry and ventilated environment far from sources of heat in original package.

Reis e Reis Indústria e Comércio Ltda

Rua Wilton Reis Costa, 220 - Cond.Ind. Eldorado

São José dos Campos / SP CEP 12238-574

Fone/Fax: (12) 3966-9977

e-mail: vendas@reisereis.com.br

Home-page: www.reisereis.com.br

Our technical advice concerning the application of the product is made verbally, in writing and through demonstration depending on the interest of the customer.

It should be noted that the application of the product is a precision process and when it is not applied by Reis e Reis, the company disclaims any responsibility; therefore, the responsibility is that of the customer. Regarding the storage and use of the product, any resulting change in its properties will be the complete responsibility of the customer.

The liability of Reis e Reis will be limited to any damage or loss in value of the goods supplied by the company and used by the customer. We guarantee the unquestionable quality of our products in accordance with our terms of sale and supply.